



**INFINITE**  
PERIPHERALS

# DPP350



## FEATURES

## PARAMETERS

<b>Printing Method</b>	Line thermal dot printing
<b>Printing Speed</b>	60mm/sec at 8.5V drive
<b>Print Width</b>	72mm
<b>Dot Density</b>	8dots/mm (203 dpi)
<b>Resident Fonts</b>	A: 12 x 24 dots    B: 9 x 16 dots
<b>Loadable Fonts</b>	C: 12 x 24 dots    D: 9 x 16 dots
<b>Printing Columns</b>	Font A, C - 48 characters per line Font B, D - 64 characters per line
<b>Logo Registration</b>	1 black & white BMP format (1-bit per pixel) Size: 576 x 248
<b>Memory</b>	1 Mega bit Flash memory
<b>Resident Barcodes</b>	EAN13, EAN8, UPC-A, UPC-E, Codebar, Code 39, Code 128
<b>Communications</b>	RS-232C and USB v1.1, compatible 2.0 Bluetooth® (optional)
<b>Readers</b>	Magnetic Card Reader - 3 track head, ISO7811 (optional) Smart Card Reader, ISO 7816-1/2/3 (optional) MIFARE Reader, ISO 14443-A (optional) SD card slot for SD card or WiFi modules (optional)
<b>Emulation</b>	ESC/POS
<b>Power Supply</b>	Rechargeable battery (Li-Ion 7.2V/2000mAh) Battery capacity: Per Charge (-30,000 lines) AC adapter - 9V @ 1000 mA
<b>Environment</b>	Operating temperature: -10°C to 50°C @ 10 to 90 % RH Storage temperature: -25°C - 70°C @ 10 - 90 % RH
<b>Reliability (MTBF)</b>	50km (printing rate 25% max)
<b>Dimensions</b>	108mm (W) x 111mm (D) x 62mm (H) without readers
<b>Weight</b>	340g (without paper); 430g (with paper)
<b>Thermal Paper</b>	80mm x 50mm diameter 58/60mm x 50mm diameter (optional)
<b>Thermal Labels</b>	Label length = 100mm maximum Diameter = 50mm, Thickness = 60 - 100 µm

3104 N Arlington Heights Rd  
Arlington Heights, IL 60004  
**Office** (847) 818-1260  
**Fax** (847) 818-1287  
**Toll-Free** (800) 278-7860  
**Email** info@ipcprint.com

1124 Main Street, Suite B  
Irvine, CA 92614  
**Office** (949) 222-0300  
**Fax** (949) 222-0375  
**Toll-Free** (866) 278-7860  
**Email** info@ipcprint.com

**ipcprint.com**